
COLOUR

1. Use ONLY CMYK colour mode when in your artwork.

The use of other colour mode such as RGB and Pantone will cause an inaccurate output of colours.


3. AVOID setting colour tints (toning) lower than 10%

Lighter shades usually print much lighter than they appear on screen and you may dissapointed with the outcome.



4. DO NOT set black colour to (C=100 M=100 Y=100 K=100)

Too much ink coverage may result in sheets sticking together and caused text or image to look blurred. To get the most from black, use the colour combinations stated below*:



^{*}However, avoid using SUPER BLACK on small text as due to ink spread.

5. For Offset and Large Format, maximum total ink coverage must not more than 240%.

Too much ink coverage may cause set off problem (sheet sticking together and caused text or image to look blurred).

For example:




6. In order to make your tint/toning effect more obvious, make sure the value between colours are at least 10% of different. it is best to put 20% and above.



LINE

1. DO NOT set line weight less than 0.25pts.


(Not applicable for Spot UV & Hot-Stamping – refer to Spot UV & Hot-Stamping section for details)



IMAGES

- 1. Ensure all the images are in CMYK colour mode.
- 2. For digital press and offset printing, ensure resolution of all your images are set to or above 300 dpi.

Scanned Line Art/Black & white images resolution are set to or above 1200dpi.



* Unless for very large size, which do not need near view, you can flexibly adjust lower the resolution.





3. DO NOT manipulate your images using a layout program*.

You are advised to manipulate your images using Adobe Photoshop. Resolution and size (dimension) are inversely proportional to each other, which means when you are enlarging the image in layout program, you are in fact lowering the resolution.







Resolution = 150 dpi

Resolution = 300 dpi

TEXT

1. Minimum font size:

4 pts (not applicable for Hot-Stamping – refer to: Hot-Stamping Artwork Specification) During printing process, minute misalignment can cause the 4 separate CMYK inks to overlap imperfectly in small text and make them look blurry. When you are working on small text, avoid:

- a. White text on a coloured or black background
- b. Light coloured text on a white background.
- c. Font types that have thin lines.





White text on a coloured or black background

Light coloured text on a white background

- d. Reverse printing (White text on coloured background made up of a combination of 2 or more CMYK Colour Value).
 - All wording that consist font size ≤5pts and without BOLD, must add outline to reduce the wording blurry problem.









Attention: AsahiArts shall not bear the consequences on the wording blurry due to small font size.

e. When you working on White background with Black text and line, you are advise to use K100 only.



2. Layout Program*: Curve / Create Outline / Path all the fonts before you convert your artwork file to PDF file format. Adobe Photoshop: Set resolution to or above 300 dpi and Rasterize Type before you save as PDF file format. We advise against setting text using Photoshop as the text will not be nearly as clear as setting text in a layout program*.